Features

Standard sizes to fit 10" through 24" square openings. Custom sizes available upon request.

For use on any flat sheet metal housing such as storage bins or conveyor enclosures

Standard 304 stainless steel construction, non-insulated. Other materials are available upon request

Poured silicone gasket with knife edge seal for a durable positive seal

Angled lower edge so that material is contained eliminating spillage when accessing vessel

Heavy-Duty Over Center latch insures seal

Available Services

- System Integration
- Industrial Ventilation
- Material Handling
- Power & Controls
- Manufacturing

For more information on any of our products or services - please visit us on the Web at:

www.steimelmetalfab.com

QUICK OPENING ACCESS DOORS



Our Quick Opening Access Doors are designed to be mounted on any flat vessel and can be bolted or welded in place at installation. These doors provide quick opening tool free access with a tight positive gasket seal.


Standard doors are offered in 10" through 24" square openings with custom sizes available upon request. Standard doors are fabricated of 304 stainless steel with a poured silicone gasket. The lower edge of the door is angled to eliminate spillage when accessing the vessel.


See the attached charted drawing for key mounting and installation dimensions.




Hamilton, OH (513) 616-8647 Steimelmetalfab.com

QUICK OPENING ACCESS DOORS







The Quick Opening Access Door is designed to be field mounted to any existing flat surfaced vessel. Field cut an opening in the vessel based on the door opening width "A" and the mounting opening height "B". The door can then be welded or bolted in place using the integral mounting flange

MODEL	"A" DOOR OPENING (SQUARE)	"B" MOUNTING OPENING HEIGHT	"C" FLANGE HEIGHT	"D" FLANGE HEIGHT
690025	10"	12-7/8"	15-3/8"	15"
690032	12"	14-7/8"	17-3/8"	17"
690059	14"	16-7/8"	19-3/8"	19"
690067	16"	18-7/8"	21-3/8"	21"
690038	18"	20-7/8"	23-3/8"	23"
690075	20"	22-7/8"	25-3/8"	25"
690083	22"	24-7/8"	27-3/8"	27"
690091	24"	26-7/8"	29-7/8"	29"

